



## GBC 240HS Home Office A3 Laminator

The GBC 240HS is a sleek and efficient solution for everyday laminating needs. Designed with both style and performance in mind, this high-speed A3 laminator is ideal for home or home office use. Boost productivity and reduce lamination time by 30% using GBC high-speed pouches. With a fast 2-minute warm-up time, it laminates a 75-micron A4 sheet in just 45 seconds, making it perfect for efficiently handling your home projects. The easy-to-use control switch offers three pouch thickness settings from 75-125 microns, providing flexibility for various document types. An anti-jam release lever ensures smooth operation by effortlessly resolving any misfed pouches. Additionally, the smart status LED system simplifies operation with clear visual and audible cues: red during warm-up, blue with a sound when ready, and an automatic shut-off after 15 minutes of inactivity to conserve energy. Protect and preserve your important documents with a perfect finish, every time.

### Attributes

- Fast warm-up time, ready to use in just 2 minutes.
- Compatible with pouches from 75 to 125 microns. Laminates ID card up to A3 sized documents.
- GBC High-Speed laminators reduce lamination time by 30% when using GBC high-speed pouches.
- Laminates 13 x A4 in 10 minutes.
- SMART status LED: glows red during warm-up and turns blue with an acoustic signal when the laminator is ready to use.
- The jam release lever allows easy manual removal of misfed or jammed pouches.
- Includes a starter pack of 5x A4 pouches (75 microns).
- Conserve energy with the 15-minute auto shut-off feature, which activates after detecting inactivity.
- Low noise level <50DbA for less distractions.
- For best results use with GBC document pouches.

### Specifications

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Laminating Speed (mm/min)      | 400                                          |
| Warm up Time (min)             | 2                                            |
| Operation Mode                 | 2 roller, no carrier, temperature controlled |
| Max. Laminating Width (mm)     | 330                                          |
| Max. Laminating Thickness (mm) | 0.5                                          |
| Max. Pouch Thickness (microns) | 75-125                                       |
| Anti-Jam Technology            | Manual release lever                         |
| Dimensions (W x H x D)         | 460 x 87 x 151 mm                            |
| Weight                         | 2200 g                                       |